

Dishwasher Metos WD-4S Basic BT



Product information

Artikelnummer	4158229
Productnaam	Dishwasher Metos WD-4S Basic BT
Afmetingen	598 × 656/967 × 820+55 mm
Gewicht	60,000 kg
Capacity	50 baskets / hour
Technical information	400 V, 10 A, 4,95 kW, 3NPE, 50 Hz, 61 dB HW: R3/4" Drain: ø 22 mm

Description

Metos WD-4S Basic BT is high-quality scandinavian manufacture; reliable and versatile undercounter dishwasher for demanding use in professional kitchens. Metos WD-4S machines have an efficient acoustic and thermal insulation. The construction is of stainless steel and tempered glass, easy to keep clean.

Metos WD-4S Basic BT has inbuilt drain and pressure booster pumps. The machine has three washing programmes; P1 for cups and glasses (wash time 1.2 min), P2 for plates (2.4 min) and P3 for cutlery and pots (4.2 min). Washing and rinsing times are programmable according to particular needs. Low temperature warning. If the rinse temperature falls below the set level, the machine goes on washing until the correct rinse temperature is reached. The stainless steel wash arms cover every millimetre of the dishware. The wash arms are emptied of washing water when the final rinse starts, ensuring that they do not drip and cause



spots on the clean items.

The self-explanatory display in tempered glass gives you a clear overview of the washing time from a distance. Colours indicate the status of the wash and a sound indicates when the wash cycle is complete. The smart display also works if you are wearing gloves or have wet hands. The machine's memory allows the reading of the number of the baskets washed, daily and for the whole usage time. Metos WD-4S Basic BT connection is three-phased, but it can be converted to one-phased on installation. Connected power for one-phase machine is 3.55kW and capacity appr. 30 baskets/h.

- three washing programmes 1.2 / 2.4 / 4.2 min
- push of button easily changes water
- space enough to wash trays up to 530 x 330 mm
- also GN1/1 canteens
- basket size 500x500 mm
- self-cleaning programme with 85°C water
- new door position keeping it slightly open
- diagnostic function
- water consumption appr. 2.4 l/basket
- booster heater 4.2 kW
- tank volume 20 l

DELIVERY INCLUDES:

- detergent dispenser
- rinse aid dispenser
- drain pump
- pressure boost pump
- tank strainers 2 pcs
- baskets for plates
- baskets for cups
- baskets for cutlery

ACCESSORIES (ordered separately):

- stand with basket rails
- stand cabinet
- water absorbent mat