Bulk brewer Metos ComBi-line 2x20 NG



Product information

SKU	4170724
Productnaam	Bulk brewer Metos ComBi-line 2x20 NG
Afmetingen	1095 × 500(360) × 895 mm
Gewicht	60,000 kg
Capacity	90 litres/hour
Technical information	380-415 V, 16 A, 9,275 kW, 3NPE, 50/60 Hz CW: 19

Description

The Metos CB 2x20 NG counter top model is an easy to use, fast and reliable coffee maker, with one filtering unit and two twenty litres containers. With its help, you will be able to brew a container full of delicious filtered coffee in fifteen minutes.

The amount of coffee to be prepared can be selected in either litres or cups from the easy to use, touch sensitive panel. The unit's touch panel helps users when it comes to using the coffee brewer and adding the correct amount of coffee powder. The coffee brewer is equipped with a timer, with the aid of which the brewing of filtered coffee can be programmed to start at a certain time. The coffee maker is capable of brewing around 90 litres (approx. 720 cups) of coffee per hour. The brewing of filtered coffee will not begin if the jug is not in place and the filter bracket has not been rotated into position above the jug. The process of brewing filtered coffee can be monitored on the panel.

The general and daily consumption of coffee and coffee powder can be monitored on the panel. When the coffee is ready, the coffee maker will let you know on the panel and with an audio signal. The measuring gauge of the electrically heated container shows how much coffee is left.
The Metos CB 2x20 NG coffee maker with container operates on the principle of flow through heating, which means that the device uses only cold and oxygen rich water during filtering, and maintains the correct temperature for water throughout the filtering processes. The indicator, which is adjusted depending on water hardness, displays the need for removing scale deposits from the coffee maker.

The coffee maker's housing and the containers are made from stainless steel, and the front parts are made from aluminium. The containers are located on the both sides of the coffee maker housing. The power connection of the insulated, electrically heated container is connected to a socket located in the housing of the coffee pot and protected from splashing.

- container capacity 20l
- filtered coffee brewing capacity around 90 l/h (approx720 cups).
- the amount of brewed filtered coffee can be selected in litres or number of cups
- filtered coffee brewing audio signal
- indictor indicating the need to remove scale deposits
- filtering bracket's boundary sensor
- container sensor
- touch sensitive screen
- table top model
- the containers are located on the both sides of the coffee maker housing

SUPPLIED SET INCLUDES:

- 2 electrically heated coffee container, with a seal equipped lid;
- 2 filtering unit with a filtering block;
- 2 mixing pipe;
- power cord for the containers
- drip tray;
- gauge glass brush;
- measuring glass;
- coffee, tea and hot water stickers

EXTRA ACCESSORIES (can be ordered separately):

- filter paper 203/533 (500 pcs per pack);
- tea filter and filling pipe;
- additional containers