

Bulk brewer Metos ComBi-line 20W NG wallmounted model



Product information

Artikelnummer 4170774

Productnaam Bulk brewer Metos ComBi-line 20W NG

wallmounted model

Afmetingen $235 \times 489 \times 901 \text{ mm}$

Gewicht 16,000 kg Capacity 90 litres/hour

Technical information 400 V, 16 A, 11,4 kW, 3NPE, 50 Hz CW: 19

Description

Metos CB 20 NG is an easy-to-use, fast and reliable wall-mounted boiler unit equipped with a hot water tap cooker unit, from which filtering takes place on a cart into a twenty litres reservoir. By combining the filtering unit with an electrically heated or insulated container and a cart that meets your needs, you get the right coffee point for your use.

The amount of coffee filtration is selectable in litres or cups on the clear touch screen of the cooker. The display of the device controls the user when using the cooker and the dispensing of the ground coffee. The cooker has a timer with which coffee filtering or the hot water system can be timed to start at a certain time. The cooker capacity is around 90 litres per hour (around 720 cups). The filter does not start if the tank is not in position and the filter arm is turned over the tank. The



flow of the filtering process can be monitored on the screen. The display can also check the total or daily consumption of coffee and coffee powder. After the coffee has been completed, the cooker informs you on the display and with the tone.

The water temperature of the hot water hose in the body is adjustable from 60°C to 97°C, factory setting at 90°C. The capacity is 60 litres of hot water per hour, single-serving 4.1 litres. The volume of the insulated boiler is 5.6 litres. The energy saving function lowers the hot water temperature to 60°C if no hot water has been used during the last two hours.

The Metos CB 20W NG coffee urn works on a flow-through heating principle, so the appliance uses only cold and oxygen-rich water in the filtration and keeps the water temperature right throughout the filtration. According to the water hardness set, the descaling need detector indicates the need for descaling of the boiler. The body is made of stainless steel, front of aluminum.

- a hot water tap
- filter capacity approx. 90 l / h (approx. 720 coffee cups), hot water 60l/h
- the filtering amount can be selected in litres or cups
- · filtering tone
- descaling need indicator
- · filter arm limit sensor
- tank detector
- the hot water temperature can be adjusted from 60 °C...97°C
- touch screen
- wall model

ACCESSORIES (to be ordered separately):

- 20 I electrically heated coffee container with sealing lid
- filter funnel for 20 I tank
- mixing tube for 20 I tank
- tea strainer for 20 I tank
- filler neck for 20 I tank
- glass hose brush
- · coffee, tea and hot water stickers
- filter paper 203/533 (500 unit packs)