

## Food transport trolley Metos Thermobox KF300 ECO



### Product information

---

SKU	4216564
Productnaam	Food transport trolley Metos Thermobox KF300 ECO
Afmetingen	930 × 770 × 1400 mm
Gewicht	150,000 kg
Capacity	10+10 x GN 1/1-65
Technical information	230 V, 1,245 kW, 1NPE, 50/60 Hz
Type of the refrigerant	R290
Quantity of refrigerant [g]	350

### Description

Metos Thermobox KF300 ECO food transport trolley is a flexible solution for simultaneous storage and transportation of warm and cold food. The trolley has two cabinets side-by-side, F-heating to the left and K-cooling to the right. The heating cabinet's hot air fan ensures safe and high-quality conditions for storage and transportation of warm food. The convection heat in the F-model reacts faster than the E-model to temperature changes and it is worth choosing whether e.g. the door is opened repeatedly during storage. The compressor-cooled K-trolley reacts more quickly to temperature changes than the C-trolley's active cooling and is a more recommended alternative, if, for example, the door is opened repeatedly during the storage period. The temperature control unit is located at the top of the trolley and has a large digital

temperature display. The temperature for the cold cabinet is displayed in blue for the warm cabinet in red.

The trolley is insulated with polyurethane, which expands under high pressure and unites the trolley's construction and the inner chambers into a strong and well-insulated unit. The trolley's energy-efficient insulation ensures safe and high-quality conditions for storage and transport of food.

The trolley can be used in small spaces. The trolley is easy to clean as its inside is completely made of stainless steel and has pressed GN guides without any joints. Large rubber wheels as well as bumpers and ergonomic handles around the trolley makes the trolley easy to handle and light. The robust doors opens comfortably by pulling the handles, which are integrated in the trolley frame. The door opens to the side, 270 degrees.

- the capacity is 10xGN1/1(warm),inner dimension: 330x540x830 mm + 10xGN1/1(cold),inner dimension: 330x540x830 mm, guide distance 80 mm
- the red cabinet on the left has a temperature range of +40°C...+90°C
- the blue cabinet on the right has a temperature range of +1°C...+9°C
- Ø160 mm wheels, two rotating with brake and two directionally locked without brake
- the wheel bracket is made of hot-dip galvanized steel
- the exterior of the two colored trolley is made of ABS plastic
- stainless steel one-hand grip handle and PVC plastic corner
- the bumper is made of galvanized steel and coated with PVC plastic
- can not be washed in a trolley washing machine, only hand wash

Accessories(charged separately):

- truck tow bar
- door with window
- two extra handles
- address card holders A4, A5, A6
- Ø200 mm wheels, two directionally locked and two with brake
- terrain wheels
- black color without extra price, own color, image or logo for extra price
- central brake