

Combi cutter Metos CC-32S



Product information

SKU	4221700
Productnaam	Combi cutter Metos CC-32S
Afmetingen	285 × 350 × 465 mm
Gewicht	7,600 kg
Technical information	230 V, 10 A, 1 kW, 1NPE, 50/60 Hz

Description

Metos Combi Cutter CC-32S Combined Vegetable Preparation machine, process up to 2 kg/minute and vertical Cutter, volume 3 litre.

Specification:

Combination machine with half-moon feed cylinder and stainless steel bowl, made to process 2kg/minute or 10-80 portions/day. Machine has two speeds with switch depending on what preparation top is mounted. Machine is controlled with a turning knob instead of buttons. Vegetable preparation top is of 0.9 litre with a tube feeder of 53mm in diameter. Bowl is 3 litre and has a scraper system with three scrapers. Knives for bowl cutter are serrated- The machine base and the knife chamber are made of ABS-plastic. Machine is controlled with a turning knob instead of buttons. Cutting tools are made of stainless steel, 185mm in diameter and washable in dishwasher. Motor rotates the cutting blade clockwise via a self-tensioned toothed belt. Machine has handles for easy mobility.

Function:

Machine for slicing, shredding, grating and cutting julienne as well as grinding, chopping, blending and mixing. Processes fruit, vegetables,

dry bread, cheese, nuts, mushrooms, meat, fish, etc.

Capacity:

Up to 80 portions/day and up to 2/kgminute. 0,9 litre feed cylinder, 53mm tube feeder for elongated products. Bowl: 3 litre.

Material:

Machine base and knives chamber: ABS-plastic. Feeder top: polycarbonate and polyamide. Cutting tools: stainless steel. Ejector plate: acetal.

Bowl: stainless steel. Knife unit: acetal. Lid and Scraper system:

Xylex.

Motor:

1.0 kW. Two speeds (500rpm, 1450 rpm) 220-240 V, single phase, 50-60 Hz.

Transmission: Toothed belt. Thermal protection.

Power Supply:

Earthed, single phase, 10A. Fuse: 10 A delayed action fuse.

Standards:

EN 1678+A1:2010. NSF/ANSI Standard 8.

Safety:

2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011

CE approved. Two safety switches, machine safety: IP34