

## Induction range Metos Flex 3.5



### Product information

---

SKU	4231310
Productnaam	Induction range Metos Flex 3.5
Afmetingen	380 × 441/460 × 138/140 mm
Gewicht	12,000 kg
Capacity	Cooking zone 372x349 mm
Technical information	240 V, 16 A, 3,5 kW, 1PE, 50/60 Hz

### Description

- continuous temperature measurement at the bottom of the pan with RTCSmp technology (Realtime Temperature Control System multi-point)
- the reliable overheat protection prolongs the service life of both the induction appliance and the cookware
- consistent power transfer over the entire cooking time for optimal cooking results
- convenient cooking without heating up the cooking environment thanks to direct heat transfer from the hob to the pan by means of induction
- easy to clean thanks to a removable, washable and reusable air filter
- cool to touch cooking surface, means no “burn on” of food debris on the cooking surface
- exceptionally robust and developed for continuous operation in the restaurant industry
- reduction of the maximum power from 100% to 25%
- mains voltage detection and automatic loading of the optimal parameters

- RTCSmp control / monitoring
- height-adjustable, locking feet
- washable air filter
- one heating zone
- ceran glass surface 372 x 349 mm
- inductor diameter ø 220 mm
- suitable pan sizes is Ø120-340 mm
- 12 power levels
- warm-holding function 25°C to 100°C
- housing of stainless steel